

ergotron[®]

moving you forward

Zido[®] Adjustable-Height Cart

- Work comfortably sitting or standing, with a height range of 30"–40" (76.2–101.6 cm)
- Choose from two widths and two lift capacities
- Standard carts lift 16–30 lbs (7.26–13.61 kg)
- Super carts lift 27–41 lbs (12.25–18.6 kg)
- Heavy cast metal base provides a strong foundation in a compact footprint. Overall weight capacity of 150 lbs (68.2 kg)
- Large 4" (10.16 cm)-diameter twin-wheel casters (two locking) take your cart everywhere you need it
- A broad range of Zido accessories helps you maximize your cart space



CONVENIENT ADJUSTABLE-HEIGHT CARTS THAT EASILY MOVE FROM A COMFORTABLE SITTING TO STANDING HEIGHT

Perfect for laptop applications! Versatile, easy-to-customize Zido carts have all the flexibility you need. Choose from dozens of accessories and outfit your Zido cart to hold a computer system, a laptop, or small devices and supplies.


Choose from two widths: 22" and 25" (55.88 and 63.5 cm), and two lift capacities: standard and super. Versatile, easy-to-customize Zido carts have all the flexibility in a compact, mobile footprint. It's perfect for healthcare, labs and general office.

Zido® Adjustable-Height Cart

EASY CONFIGURABILITY WRAPPED IN A SLEEK AND COMPACT DESIGN



Adjust the main worksurface 30"–40" (76.2 cm–101.6 cm) high with the squeeze of a lever



The column has holes in 1" (2.54 cm) increments to install accessories at the right height



Zido's heavy cast metal base provide a stable foundation in a compact footprint



Worksurface is wrapped in a highly durable thermoplastic laminate to resist cracking and stand up to a wide range of chemicals

	Zido Adjustable-Height Cart, 22	Zido Adjustable-Height Cart, 25 Light Load	Zido Adjustable-Height Cart, 25 Heavy Load
Part # (color)	ZAL22CG/CG4 (cool grey)	ZAL25CG/CG4 (cool grey)	ZAH25CG/CG4 (cool grey)
Materials and Finishes	The steel column and cast metal base receive a baked-on powder coated finish that's durable and easy to clean. Worksurface is 0.75" (2 cm)–thick medium density fiberboard wrapped in Comfort Edge thermoplastic laminate that resists cracking and chipping and stands up to a wide range of chemicals		
Column Height Range	30" (76.2 cm) to 40" (101.6 cm)		
Optimal Load *	16-30 lbs. (7.3–13.6 kg)		27-41 lbs. (12.3–18.6 kg)
Weight Capacity*	150 lbs (68.2 kg) in total; 40 lbs (18.2 kg) on worksurface.		
Base Dimensions	17"W x 22.25"D (43.18 x 56.52 cm)	21"W x 25.75"D (53.34 x 65.41 cm)	
Worksurface Dimensions	22" x 17" (56 x 43 cm)	25" x 20.5" (63.5 x 52.07 cm)	
Mobility	Easy to move with 4" (10.16 cm) twinwheel rubber casters (two locking). Heavy cast metal base provides stability		
Product Weight	40 lbs. (18 kg)	53 lbs. (24 kg)	
Shipping Weight	50 lbs (22.7 kg)	63 lbs (28.6 kg)	
Shipping Dimensions	19.35" x 29" x 7" (18 x 89 x 74 cm)	35" x 29" x 7" (18 x 89 x 74 cm)	
Warranty	Limited lifetime; five (5) years for pneumatic cylinder		

* Weight Capacity: 150 lbs (68.2 kg) in total; 40 lbs (18.2 kg) on worksurface. Note: Optimal load on adjustable-height worksurface = 16–30 lbs (7.3–13.6 kg); loads lighter than 16 lbs (7.3 kg) will be harder to push down and loads heavier than 30 lbs (13.6 kg) will be harder to pull up. When calculating the load being applied to the cart's column and worksurface, also factor the weight of any accessory options that are being installed

Download additional resources at ergotron.com.

For more information:

Americas: 800.888.8458 / +1.651.681.7600 / insidesales@ergotron.com

EMEA: +31.33.45.45.600 / info.eu@ergotron.com

APAC: apaccustomerservice@ergotron.com

Custom: custom@ergotron.com

© Ergotron, Inc. 04.21.2020

Literature made in the U.S.A. Content subject to change.

Ergotron devices are not intended to cure, treat, mitigate or prevent any disease.

Patent information available at www.ergotron.com/patents.

WorkFit, StyleView, LearnFit, Neo-Flex, PowerShuttle, LiFeKinnex, CareFit and eKinnex are trademarks of Ergotron.

